





| | | |
|---|---|---|
|  | <div>  </div> <div>  </div> <div>  </div> | <div> Adapted to DIN VDE 0285, DIN EN 50525 </div> <div> HFFR insulated and HFFR sheathed flexible, halogen-free, extremely fire-resistant screened control cable </div> |
|---|---|---|

Construction:

| | |
|--------------------------------|---|
| Conductors: | annealed copper flexible conductor, class 5 acc. to DIN VDE 0295 |
| Insulation: | special halogen-free compound |
| Core identification: | -JZ: one core green-yellow, all other cores black with continuous white numbering to DIN VDE 0293 -OZ: all cores black with continuous white numbering to DIN VDE 0293 |
| Taping and screening: | tinned copper braided screen (approx. 85% coverage) |
| Outer sheath: | special halogen-free compound |
| Colour of outer sheath: | black RAL 9005 |

Characteristic:

| | |
|---------------------------------------|---|
| Nominal Voltage: | 600/1000 V |
| Test voltage 50Hz: | 4000 V |
| Temperature range: | flexing: -15°C to +70°C fixed: -40°C to +70°C |
| Minimum bending radius: | free movement: 15 x cable Ø fixed installation: 7,5 x cable Ø |
| Flame propagation: | acc. to DIN VDE 0482-332-1-2, DIN EN 60332-1-2, IEC 60332-1-2 |
| Standard length cable packing: | 500 m or 1000 m on drums. Other forms of packing and delivery are available on request. |

Application:

Halogen-free, flame retardant cables are used as measuring and control cables in machine tools, conveyor belts, production lines as well as in plant installations. For fixed or flexible applications with medium mechanical strain. Suitable for the application in dry, damp and wet rooms and also for laying on, in and under plaster as well as in concrete and masonry excluding in direct laying in shaken or stamped concrete, not suitable for imbedding in solidified or compressed concrete. Copper screening offers increased electromagnetic compatibility and disturbance-free transmission of signals and impulses

| Number and nominal cross-sectional area of conductors | Approximate overall diameter | Approximate net weight of copper | Approximate net weight of cables |
|---|------------------------------|----------------------------------|----------------------------------|
| n x mm ² | mm | kg/km | kg/km |
| 3 x 0,5 | 8,8 | 45,0 | 150,0 |
| 4 x 0,5 | 9,4 | 54,0 | 170,0 |
| 5 x 0,5 | 10,2 | 66,0 | 199,0 |
| 7 x 0,5 | 10,8 | 79,0 | 235,0 |
| 12 x 0,5 | 14,3 | 137,0 | 320,0 |
| 18 x 0,5 | 16,4 | 156,0 | 428,0 |
| 25 x 0,5 | 19,3 | 250,0 | 503,0 |
| 3 x 0,75 | 9,1 | 57,0 | 155,0 |
| 4 x 0,75 | 9,9 | 63,0 | 190,0 |

| | | | | | |
|----|---|------|------|--------|--------|
| 5 | x | 0,75 | 10,6 | 76,0 | 228,0 |
| 7 | x | 0,75 | 11,5 | 100,0 | 323,0 |
| 12 | x | 0,75 | 14,9 | 175,0 | 410,0 |
| 18 | x | 0,75 | 17,2 | 240,0 | 560,0 |
| 25 | x | 0,75 | 20,6 | 306,0 | 730,0 |
| 3 | x | 1 | 9,8 | 64,0 | 163,0 |
| 4 | x | 1 | 10,4 | 76,0 | 200,0 |
| 5 | x | 1 | 11,4 | 89,0 | 239,0 |
| 7 | x | 1 | 12,3 | 114,0 | 289,0 |
| 12 | x | 1 | 15,9 | 186,0 | 464,0 |
| 18 | x | 1 | 18,2 | 284,0 | 628,0 |
| 25 | x | 1 | 22,0 | 387,0 | 855,0 |
| 3 | x | 1,5 | 10,8 | 82,0 | 187,0 |
| 4 | x | 1,5 | 11,5 | 99,0 | 240,0 |
| 5 | x | 1,5 | 13,0 | 123,0 | 289,0 |
| 7 | x | 1,5 | 14,2 | 148,0 | 383,0 |
| 12 | x | 1,5 | 18,4 | 274,0 | 592,0 |
| 18 | x | 1,5 | 21,3 | 386,0 | 806,0 |
| 25 | x | 1,5 | 25,4 | 531,0 | 1241,0 |
| 3 | x | 2,5 | 12,8 | 148,0 | 298,0 |
| 4 | x | 2,5 | 13,8 | 169,0 | 345,0 |
| 5 | x | 2,5 | 15,0 | 220,0 | 427,0 |
| 7 | x | 2,5 | 16,3 | 284,0 | 561,0 |
| 12 | x | 2,5 | 21,6 | 470,0 | 857,0 |
| 18 | x | 2,5 | 25,2 | 572,0 | 1355,0 |
| 25 | x | 2,5 | 30,0 | 740,0 | 1995,0 |
| 3 | x | 4 | 14,6 | 178,0 | 391,0 |
| 4 | x | 4 | 15,7 | 234,0 | 527,0 |
| 5 | x | 4 | 17,2 | 284,0 | 700,0 |
| 3 | x | 6 | 15,9 | 245,0 | 629,0 |
| 4 | x | 6 | 17,4 | 316,0 | 731,0 |
| 5 | x | 6 | 19,2 | 442,0 | 1105,0 |
| 3 | x | 10 | 19,8 | 367,0 | 1125,0 |
| 4 | x | 10 | 21,5 | 549,0 | 1345,0 |
| 5 | x | 10 | 23,5 | 604,0 | 1635,0 |
| 4 | x | 16 | 25,7 | 807,0 | 1395,0 |
| 5 | x | 16 | 28,5 | 940,0 | 1870,0 |
| 3 | x | 25 | 28,2 | 920,0 | 2465,0 |
| 4 | x | 25 | 31,3 | 1169,0 | 2750,0 |
| 5 | x | 25 | 34,5 | 1420,0 | 3490,0 |