

	  	SPEAKER CABLE
		PVC insulated and PUR sheathed flexible speaker cable

Construction:	
Conductor:	annealed copper flexible conductor, class 5 acc. to DIN VDE 0295
Insulation:	special PVC compound
Core identification:	red and black
Outer sheath:	PUR
Colour of outer sheath:	black
Characteristic:	
Temperature range:	-25°C to +80°C
Minimum bending radius:	33 mm
Standard length cable packing:	500 m or 1000 m on drums. Other forms of packing and delivery are available on request.

Application:
Extremely flexible sound cable. Wires used in mobile applications, studios etc. Resistant to abrasion. For outdoor use.

Number and nominal cross-sectional area of conductors n x mm ²	Conductor resistance Ω/km	Approximate overall diameter mm	Approximate net weight of copper kg/km	Approximate net weight of cables kg/km
2 x 1,5	< 12,7	6,6	28,8	66,9
2 x 2,5	< 7,9	7,5	48,0	98,5
2 x 4,0	< 4,9	9,4	76,8	150,2
4 x 2,5	< 7,9	8,8	96,0	159,1
4 x 4,0	< 4,9	11,6	153,6	253,0
8 x 2,5	< 7,9	13,5	192,0	332,1
8 x 4,0	< 4,9	16,8	307,2	499,5