

	  	SPEAKER CABLE
		FRNC insulated and FRNC sheathed flexible speaker cable

Construction:	
Conductor:	annealed copper flexible conductor, class 5 acc. to DIN VDE 0295
Insulation:	special PVC compound
Core identification:	red and black
Outer sheath:	special halogen-free compound
Colour of outer sheath:	black
Characteristic:	
Temperature range:	-5°C to +70°C
Minimum bending radius:	33 mm
Standard length cable packing:	500 m or 1000 m on drums. Other forms of packing and delivery are available on request.

Application:
Extremely flexible sound cable. Wires used in mobile applications, studios etc. Fireproof, halogen-free.

Number and nominal cross-sectional area of conductors	Conductor resistance	Approximate overall diameter	Approximate net weight of copper	Approximate net weight of cables
n x mm ²	Ω/km	mm	kg/km	kg/km
2 x 1,5	< 12,7	6,6	28,8	77,0
2 x 2,5	< 7,9	7,5	48,0	105,6
2 x 4,0	< 4,9	9,4	76,8	166,9
4 x 2,5	< 7,9	8,8	96,0	161,5
4 x 4,0	< 4,9	11,6	153,6	271,6
8 x 2,5	< 7,9	13,5	192,0	338,6
8 x 4,0	< 4,9	16,8	307,2	531,5